

AC-D405Z (2,7-13,5mm)

Analog 4in1 camera 5Mpx - Motorized



Main features:

- Analog 4in1 camera
- Support for AHD / TVI / CVI / CVBS standards
- 5Mpx converter
- IR up to 40m
- Resolution 2560 × 1944 @ 20fps
- Motorized zoom lens 2.7-13.5mm
- Smart IR function

AC-D405Z (2,7-13,5mm)

Analog 4in1 camera 5Mpx - Motorized



Camera	
Image sensor	5Mpx CMOS
Resolution	2560 (H) × 1944 (V)
Sensitivity	0.01 Lux@(F1.2,AGC ON), 0 Lux z IR
Shutter time	PAL: 1/25 s do 1/50, 000 s NTSC: 1/30 s do 1/50, 000 s
Lens :	Motorized 2.7-13.5mm @ F1.4
Horizontal Viewing Angle:	95.7° - 29.1°
Lens Mount	Φ 14
Day / Night	IR cut filter
Adjustment range	Pan: 0° do 355°, Tilt: 0° do 75°, Rotate: 0° do 355°
Synchronization	Internal
Frame Rate	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps
Menu	
AGC	Yes
Day / Night mode	Auto / Color / BW (Black and White)
White Balance	ATW/MWB
BLC	Yes
DWDR	Yes
Language	English
Functions	Brightness, Sharpness, DNR, Reflection, Smart IR
Connectors	
Video output	1x analog HD output
Switch modes	TVI/AHD/CVI/CVBS
General	
Working environment	-40 ° C to 60 ° C, Humidity 90% or less (non-condensing)
Power Supply	12 VDC ±25%
Power consumption	Max. 6.3 W
IP Class	IP67
Case	Metall
IR Range	Up to 40 m

AC-D405Z (2,7-13,5mm)

Analog 4in1 camera 5Mpx - Motorized



Communication	Via coaxial cable (TVI mode)
Dimensions	123.86 mm × 134.3 mm × 110.11 mm (4.88" × 5.29" × 4.38")
Weight	approx. 580 g (1.28 lb.)

