

Analog camera ,2 MPX ,DarkFighter , MOTO lens : 2.7-13.5mm

AC-T402Z-DF , Motorized Lens :2.7-13.5mm



Main Features :

- Image transfer standard : TVI/AHD/CVI/CVBS
- Image Sensor : 2MP Progressive Scan **STARLIGHT – ULTRA LOW LIGHT**
- Resolution : 1920x1080 / 25 kl/s (PAL)
- Number of Pixels : 2Mpx
- Sensitivity : 0.005 lux/F1.2 (AGC ON), 0 lux (IR LED On)
- Lens : 2.7 – 13.5 mm @ F1.4 Motozoom
- Smart IR range up to 70m
- AES, AGC, DNR
- WDR 120dB
- ICR mechanical infrared filter
- Protection Level : IP67
- Power Supply : 12V DC

Specifications

Camera	
Image Sensor	2 Mpx CMOS progressive scan
Supported video systems	AHD, CVI, TVI, CVBS (PAL/NTSC)
Sensitivity	Minimum : 0.005 Lux @(F1.2, AGC ON), 0 Lux with IR on
Electronic shutter	1/25 (1/30) s to 1/50,000 s
Lens	2.7 - 13 mm @ F1.4, horizontal (horizontal) field of view 102 ° - 31 °
Lens Mount	Φ14
Day / night mode	IR cut cut-off filter with automatic switching
Installation in 3 axes	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°
Synchronization	Internal
WDR (wide dynamic range)	>120dB
Video output	1x 1V p-p, BNC, 75Ω
Picture	
Maximum resolution	1920 × 1080
Frame & resolution	25 kl/s @ 1920×1080 (1080p) - PAL 30 kl/s @ 1920×1080 (1080p) - NTSC
Image enhancement functions	AGC, AES, DNR, 3D DNR, Brightness, Sharpness, Mirror image, Smart IR, Day-night mode, BLC
Menu OSD	Yes
Other features	
Working temperature & humidity	-40 ° C to 60 ° C (-40 ° F to 140 ° F), humidity: 90% or less (non-condensing)
Power Supply	12 VDC ± 25% / 1x 5.5 / 2.1 socket on the cable
Power consumption	Max. 7.7 W
Protection Level	IP 67
IR Range	Up to 70m
Dimensions	84.5mm×92mm×255.1mm (3.33"×3.62"×10")
Weight	approx. 648g (1.43lb)

Dimensions

