

Camera 4w1 AC-D405FA

Short specification

- Resolution : **5 MPx**
- IR Range: **Up to 40m**
- **TVI/AHD/CVI/CVBS**
- **Built-in microphone**



Camera		
Image Sensor		5 MP CMOS
System		PAL/NTSC
Resolution		2560 (H) × 1944 (V)
Frames		TVI: 5M@20fps, 4M@30fps, 4M@25fps, 1080p@30fps, 1080p@25fps AHD: 5M@20fps, 4M@30fps, 4M@25fps CVI: 4M@30fps, 4M@25fps CVBS: PAL/NTSC
Sensitivity		0.01 Lux@(F1.2, AGC ON), 0 Lux IR on
Shutter		PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Lens		2.8 mm
FOV		HFOV: 85°, VFOV: 63°, DFOV: 110°
Lens Mount		M12
Day & Night		ICR
WDR (Wide Dynamic Range)		Digital WDR
Audio		Built-in microphone
Position Adjustment		Rotation: 0° - 360°, Tilt: 0° - 75°, Rotation: 0° - 360°
Menu		
Picture Mode		STD/HIGH-SAT
AGC		Yes
Day/ Night Mode		Auto/Color/BW (Black and White)
White Balance		Auto/Manual
Mode AE (Auto Exposure)		DWDR/BLC/HLC/Global
Noise reduction		2D DNR
Language		English
Functions		Brightness, Sharpness, Mirror, Smart IR
Interface		
Video output		Switchable TVI/AHD/CVI/CVBS

General

Working enviroment	-40°C to 60°C (-40F to 140°F), Humidity: 90% or less (no condensation)
Power Supply	12 VDC ± 25%
Power consumption	Max. 4.3 W
Level of Protection	IP67
Material	Metal & plastic
Ir Range	Upto 40m
Communication	HIKVISION-C
Dimensions	Φ 109.82 mm × 91.03 mm (Φ 4.32" × 3.6")
Weight	approx. 303 g (0.67 lb.)

Dimensions

