



Camera 4w1 AC-CV-T205F/L 2.8mm

Short Specifications:

- Resolution 5 MP, 2560 × 1944
- Smart light, white light range up to 20m
- 130 dB true WDR, 3D DNR
- Lens 2.8 mm fixed focal
- 24h color image - ColorVu
- 4 in 1 video output (switchable TVI / AHD / CVI / CVBS)

Camera	
Image sensor	5 MP CMOS
Sensitivity	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light on
Shutter	PAL: 1/25 s do 1/50, 000 s NTSC: 1/30 s do 1/50, 000 s
Day / Night	Color
Shutter	Yes - Max. 16 times
Setting position	Rotation: 0 to 360 °, Tilt: 0 to 90 °, Rotation: 0 to 360 °
Strobe light alarm	Yes
WDR	130 dB
Lens	
Lens type & FOV	2.8 mm, HFOV: 99.7°, VFOV: 72°, DFOV: 139.8°
Aperturæ	F1.4
Lens Mount	M16
Aperture type	Fixed
Menu	
White light	Auto/Off
Picture Mode	STD/HIGH-SAT
AGC	Yes

White Balance	Auto/Manual
AE (Auto Exposure) Mode	WDR/BLC/HLC/Global/HLS/Anti-banding
Privacy masks	4 programmable privacy masks
Motion detection	YES
Language	English
Functions	Brightness, Sharpness, Mirror, Smart Light
Lighting	
Range of white ligh	Up to 20 m
Illuminator	LED
Video	
Max. Resolution	2560 (H) × 1944 (V)
Frames	TVI: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080p@30fps, 1080p@25fps
	CVI: 4MP@30fps, 4MP@25fps
	AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps
	CVBS: PAL/NTSC
General	
Working Enviroment	40 ° C to 60 ° C (-40 ° F to 140 ° F), Humidity 90% or less (no condensation)
Power consumption	3.5W
Power Supply	12 VDC
Material	Metal
Power interface	Ø5.5 mm coaxial power plug
Weight	approx 350 g (0.77 lb.)
Dimensions	68 mm × 70 mm × 168.2 mm (2.68" × 2.76" × 6.62")
Protection Level	IP67

Dimensions

