

XVR-814ID4AA HYBRID



Main features::

- Camera support standards: TVI / AHD / CVI / CVBS / IP
- Support for long distance video transmission TVI 720p to 1200m, TVI 1080p to 800m
- Compression format: H.265 Pro + / H.265 Pro / H.265 / H.264 + / H.264
- Support for 4-5 Mpx BNC cameras
- Video outputs: HDMI/VGA
- Cooperation with IP cameras up to 6MPX (max 12 IP cameras)
- Support for cameras with built-in image analytics (VCA)
- **AcuSense image analytics on 4 channels (people / vehicle detection) or face detection on 1 channel**
- 10TB sata disk support
- Power Supply : 12V DC
- **Recorder equipped with additional connectors: 16 x AUDIO-in / 4 X ALARM-in / 1 x ALARM-out**

SPECYFIKACJA

Basic	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Supported video systems	AHD, CVI, TVI, CVBS (PAL/NTSC)
BNC inputs	8
HDTVI inputs	4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25
AHD inputs	4 MP, 1080p25, 1080p30, 720p25, 720p30
HDCVI inputs	1080p25, 1080p30, 720p25, 720p30
CVBS inputs	PAL/NTSC
IP Connection	2 channels up to 6MP, 4 channels up to 4MP with disable BNC analog 10-12 channels up 6/4MP Video Compression: H.265+/H.265/H.264+/H.264 Audio Compression: G.711u
Audio Input	1-Channel 2.0V p-p, RCA, 1K Ω
Image And Audio	
HDMI/VGA output	VGA: 1-channel 1920x1080/1280x1024/60Hz: 1280x720/60Hz 1024x768 HDMI: 1-channel 4K(3840x2160)30Hz/2K(2560x1440)60Hz/1280x1024 60Hz/ 1280x720 60Hz/1024x768 60Hz/1024x768 60Hz
Encoding resolution	4 MP/3 MP/1080p/WD1/4CIF/VGA/CIF
Encoding resolution	Main stream: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps)
	Second stream: WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)
Data transfer rate	32Kbps - 6 Mbps
Audio output	1-channel, RCA, 1K Ω
Stream type	Video/Video Audio
Audio speed	64 Kbps
Dual stream	Yes
Network	
Synchronous playback	8 channels
Bandwith	32 Mbps
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Connecting to the network	1x RJ45 10M/100M/1000M
Connectors	
Audio & alarm	8 x AUDIO-in / 8 X ALARM-in / 4 x ALARM-out
Interface	1x Sata 10 TB HDD
Software	
Programs	MWCLIENT (PC)/MWAPP (ANDROID)/MWAPP (IOS)
Other features	
USB inputs	2x USB 2.0
Working enviroment	-10 ° C to 55 ° C (+40 ° F to 131 ° F) 90% humidity
Power Supply	12 VDC
Power consumption	18W
Dimensions/Weight	315mm x 242mm x 45mm (12.4"x9.5"x1.8") / 2 kg