

Analog camera fixed lens ,
2Mpx, AC-D202F-G-I , 2.8mm, 4in1



Main Features :

- Image transfer standard: TVI/AHD/CVI/CVBS
- Transducer: 2MP
- Resolution: 1920x1080
- Number of pixels: 2Mpx
- Sensitivity : 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
- Lens : 2.8mm
- Smart IR floodlight with a range of 20m (IR ON / OFF function)
- AGC,BLC,
- Housing: protection class IP66 (metal housing)
- Power Supply: 12V DC

SPECIFICATIONS

Basic	
Converter	2Mpx CMOS progressive scan
Video systems supported	AHD, CVI, TVI, CVBS (PAL/NTSC)
Sensistivity	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Electronic Shutter	1/25 (1/30) s to 1/50,000 s
Lens	2.8 mm, horizontal field of view 103 °
Lens Mount	Φ12
Day / night mode	IR cut cut-off filter with automatic switching
Installation in 3 axes	Vertical rotation: 0 ° to 360 °, Tilt: 75 °, Rotation: 0 ° to 360 °
Synchronization	Internal
Video Output	1x 1V p-p, BNC, 75Ω
Picture	
Maximum resolution	1920 × 1080
aFrames and resolution	25 kl/s @ 1920×1080 (1080p) - PAL 30 kl/s @ 1920×1080 (1080p) - NTSC
Picture enhancement functions	AGC,BLC,DWDR
Menu OSD	
AGC Selection	High / Medium / Low / Off
Day / night mode	Auto/Color/BW (Black and White)
Backlight Compensation BLC	On/Off
DWDR	On/Off
Menu Language	English
Additional functions	Brightness, Sharpness, DNR, Mirror, Smart IR
Other features	
Working temperature and humidity	-40 ° C to 60 ° C (-40 ° F to 140 ° F), humidity: 90% or less (non-condensing)
Power Supply	12 VDC ± 25% / 1x 5.5 / 2.1 socket on the cable
Power consumption	Max. 4W
Tightness class	IP 66
IR Range	Up to 20m
Dimensions	82.6mm×69.66mm (3.38" × 2.74")
Weight	approx. 230g (0.51 lb.)

Dimensions

