

NVR-814K-I

8 - channel IP recorder - 8mpx



Main features:

- 8-channel IP recorder
- Supported resolutions 8Mpx @25fps, 4Mpx @ 30fps, 1080p @ 30fps
- Synchronous playback of 8 channels
- HDMI 4K output
- Remote access via a mobile application MWAPP and the MWCMS program
- Ability to write data to diskDropbox, Google Drive or Microsoft OneDrive
- Supports hard disk up to 6TB

NVR-814K-I

8 - channel IP recorder - 8mpx



Audio / Video inputs	
IP camera inputs	4-ch (up to 8MP)
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ)
Incoming band	80 Mbps
Outgoing band	80 Mbps
Audio / Video outputs	
Recording resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
HDMI output	1-ch, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA output	1-ch, 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Audio output	1-ch, RCA (Line, 1 kΩ)
Encoding format	H.265/H.265+/H.264/H.264+/MPEG4
Resolution preview / playback	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	8-ch
Decoding ability	1-ch @ 8 MP / 4-ch @ 1080p
Network	
Protocols	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
Dysk twardy	
SATA	1 SATA connectors
Disc capacity	Up to 6TB
Connectors	
Network connectors	1, RJ45 10M/100M/1000M
USB inputs	2 × USB 2.0
General	
Power supply	12 VDC
Power consumption	≤ 18 W
Without HDD	≤ 10 W
Working enviroment	-10 °C do +55 °C (+14 °F do +131 °F)
Working environment humidity	10% do 90%

NVR-814K-I

8 - channel IP recorder - 8mpx



Case - Rack	1U
Dimensions (W × D × H)	315 × 240 × 48 mm (12.4" × 9.4" × 1.9")
Weight (without HDD)	≤ 1 kg (2.2 lb)