

PRODUCT DATASHEET

HQI-TS 150 W/D

POWERSTAR HQI®-TS EXCELLENCE | Metal halide lamps with quartz technology for enclosed luminaires



Areas of application

- Shop interiors, shop windows
- Shopping arcades
- Foyers, reception areas
- Buildings, monuments, bridges
- Museums, exhibitions
- Exhibition halls and trade fairs
- Pedestrian zones, public squares
- Parks and gardens
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- High efficiency
- Uniform distribution of light
- Good to excellent color rendering
- Long lifetime
- Hot restrike capable
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

Product features

- POWERSTAR® quartz technology
- Light colors: warm white (WDL), neutral white (NDL), daylight (D), cool daylight (CD)
- Average lifetime: 12,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	150 W
Construction wattage	156.60 W
Nominal voltage	100 V
Ignition voltage	13304 kVp ¹⁾
Nominal current	1.8 A
PFC capacitor at 50 Hz	20 µF

¹⁾ Minimum / Maximum

Photometrical data

Luminous flux	13000 lm
Luminous efficacy	86 lm/W
Color temperature	5450 K
Color rendering index Ra	≤ 81
Light color	854
UV protection	Yes

Dimensions & Weight

Overall length	135.00 mm
Length	135.00 mm
Light center length (LCL)	66,0 mm
Width (incl. round luminaires)	23 mm
Height (incl. round luminaires)	23 mm
Diameter	23 mm
Product weight	22.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	450 °C
Maximum permitted pinch temperature	350 °C

Lifespan

Nominal lamp life time	12000 h
Lifespan B50	12000 h

Additional product data

Base (standard designation)	RX7s-24
Mercury content	13.0 mg
Design / version	Clear
System guarantee level	3 (1/5)

Capabilities

Dimmable	No
Burning position	p45
Enclosed luminaire required	Yes
Hot restart	Yes

Certificates & Standards

Energy efficiency class	G
Energy consumption	157.00 kWh/1000h

Country-specific categorizations

ILCOS	MD/UB-150/856-H/E/SL-RX7s=24-23/135/H
Order reference	HQI-TS 150W/D/E

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	MH
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	RX7s-24
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Chromaticity coordinate x	0,335
Chromaticity coordinate y	0,348
Beam angle	SPHERE_360
LED light source replaces a fluorescent light source	not applicable
EPREL ID	546550
Model number	AC34324

DOWNLOAD DATA**DOWNLOAD DATA**

User instruction

Declarations of conformity
EC Declaration of Conformity - 2021 9C1-4072118-EN-01 - HQI

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321678409	Folding box 1	141 mm x 31 mm x 35 mm	32.00 g	0.15 dm ³
4008321678416	Shipping box 12	154 mm x 156 mm x 116 mm	498.00 g	2.79 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For more information on the system guarantee and the terms and conditions of the guarantee visit www.ledvance.com/system-guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.