



2-Port Power Delivery Mini Car Charger - 25 W

USB-C Power Delivery Port up to 25 W, USB-A QC 3.0 Charging Port up to 18 W,
Black

Part No.: [102414](#)

EAN-13: 0766623102414 | UPC: 766623102414

Power up your devices with a powerful Power Delivery car charger.

Enjoy incredible mobile charging power with the Manhattan 2-Port Power Delivery Mini Car Charger - 25 W. The USB-C port's Power Delivery (PD) technology determines the power needs of your connected MacBook®, smartphone, tablet, handheld game console or other device and delivers it at the fastest, safest rate. The additional USB-A port fast charges an additional handheld device with QC 3.0 technology, which returns your device to full power far quicker than a standard charger. No matter your vehicle, this compact charger fits most 12 - 24 V auxiliary power sockets, so it's the perfect power companion to have on hand for when your devices' batteries are low and a standard wall outlet is not available. The Manhattan 2-Port Power Delivery Mini Car Charger - 25 W also intelligently protects itself and your devices from short-circuits, overvoltage, overcurrent and overheating.

Features:

- Two-device charging solution with USB-C Power Delivery (PD 3.0) and USB-A QC 3.0 charging ports
- Charges two different devices simultaneously with total power up to 25 W
- USB-C Power Delivery (PD) port delivering up to 25 W
- USB-C Power Delivery (PD) port delivering up to 25 W to charge a smartphone, tablet, GPS, handheld game console and more
- QC 3.0 charging port delivering up to 18 W
- Overload, overcurrent and overheat protection

- Ultra-compact, portable and lightweight design for easy travel
- Fits most vehicles' 12 - 24 V auxiliary power socket
- Three-year warranty

Specifications:

Standards and Certifications

- PD 3.0
- Qualcomm QC 3.0
- CE
- RoHS
- FCC

Electrical

- DC input: 12 - 24 V; 50 - 60 Hz
- Voltage/current settings (maximum):
 - USB-C PD 25 W output:
 - 5 V / 3 A
 - 9 V / 3 A
 - 12 V / 2.5 A
 - 15 V / 2 A
 - 20 V / 1.5 A
 - USB-A QC 3.0 18 W output:
 - 4.5 V / 5 A
 - 5 V / 4.5 A
 - 9 V / 3 A
 - 12 V / 2.5 A

Protection Characteristics

- Short-circuit (SCP) with auto-recovery mode
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 150% (max)
- Over-temperature (OTP)

Physical

- Dimensions: 45 x 26 x 26 mm (1.77 x 1.02 x 1.02 in.)
- Weight: 40 g (1.41 oz.)
- Housing: plastic

Operating Environment

- Operation temperature: -20 - 55°C (-4 - 131°F)
- Storage temperature: -40 - 70°C (-40 - 158°F)
- Humidity (noncondensing): 5 - 75% RH

Package Contents

- 2-Port Power Delivery Mini Car Charger - 25 W
- Quick Instruction Guide



