



# A14B1K11

|                                       |                                  |                   |
|---------------------------------------|----------------------------------|-------------------|
| Connection Type                       | with Terminal                    |                   |
| Print                                 | (0-I) Marked                     |                   |
| Product                               | Rocker Switch                    |                   |
| Contact                               | 2NO                              |                   |
| Color                                 | Red                              |                   |
| Illumination                          | with Illumination                |                   |
| Dia                                   | 30*22mm                          |                   |
| Current                               | Ie                               | 16 A (250V AC)    |
| Usage Category                        | AC15                             |                   |
| Mechanical Life                       | Min Qty                          | 50000             |
| Electrical Life                       | Min Qty                          | 50000             |
| Operating Frequency                   | On-Off/Hour                      | Mech.900 Elec.900 |
| Insulation Voltage                    | Ui                               | 300 V             |
| Impulse Withstand Voltage             | Uimp                             | 2.5 kV            |
| Dielectric Strength (Body-Contact)    | 2.500V AC                        |                   |
| Dielectric Strength (Contact-Contact) | 1.500V AC                        |                   |
| Isolation Resistance                  | 10 MΩ min. (500V DC)             |                   |
| Operating Temperature                 | -25 / +80 °C                     |                   |
| Pollution Degree                      | 3                                |                   |
| Protection Degree                     | IP20                             |                   |
| Contact Material                      | AgNi                             |                   |
| Cable Section                         | Terminal 6,3*0,8 mm              |                   |
| Short Circuit Breaking Capacity       | Ics                              | 1 kA              |
| Serial                                | A14 Series                       |                   |
| Body Color                            | Black Body                       |                   |
| Specifications                        | With or w/o illumination options |                   |
|                                       | Four different color options     |                   |
|                                       | Black or white body              |                   |

Snap action

Standards / Certificates

TS EN 61058-1

