



PLIABLE CONDUITS

COMBO SPIRAL WITH WIRE

LIGHT TYPE 320N

TECHNICAL DATA SHEET

Reference:	LVD 2014/35/EU			
Directives & Standards:	EN 61386-1:2008 Cable Management General Requirements			
	EN 61386-22:2004 + A11:2010 Pliable Conduit Systems			
RoHS Compliant:	2022/95/EC Restriction of Hazardous Substances, RoHS			
Applications	Indoor			
Installations	Residential and Industrial Installations			
	Cable Routing through Masonry - Flush Installations			
Characteristics:	Corrugated (spiral), Pliable			
	Coil Packaging			
	Self Extinguishing - Flame Retardant			
Structural Material:	Polyvinyl Chloride (U-PVC)			
Classification: EN 61386-1	2221			
Compression Resistance:	320N / 5cm - 2			2 
Impact Resistance:	m:1.0 kg / h:100mm - 2			2 
Temperature Range:	- 5 °C - 2			2  1
	+ 60 °C - 1			
Bending Resistance:	Pliable - 2			
Electrical Properties:	Dielectric Strength:	2kv/15min	Insulation Resistance:	>100MΩ
Color / available:	Grey (RAL 7035)			

TYPE:	16	20	25	32
CODE:	31-21037-016	31-21038-020	31-21039-025	31-21040-032
Outside Ø D ₁ / mm	16	20	25	32
Inside Ø D ₂ / mm	11,5	15,3	19,2	25,4
COIL / m	200	200	50	50